



Analog

Цилиндрические

HCO-6070R

1080p аналоговая HD цилиндрическая камера с ИК-подсветкой



Key Features

- Разрешение Full HD
- 0,11 лк при F1.6 (цветн.), 0 лк (Ч/Б : ИК светодиод вкл.)
- Вариофокальный объектив 3,2 ~ 10 мм (3,1x)
- Дневной и ночной (с выдвигаемым ИК фильтром) режимы, WDR (120 дБ)
- SSNRIV, обнаружение движения
- Дальность видимости с ИК подсветкой 30 м, IP66, IK10
- Дальность передачи макс. 500 м
- Простая установка (Plug & play), двойное питание

Compatible Accessories (Optional)



SBO-100B1



SBP-302PM

HCO-6070R

1080p аналоговая HD
цилиндрическая камера с ИК-
подсветкой



Specifications

Video

Imaging Device	1/2.8" 2MP CMOS
Resolution	1920x1080
Max. Framerate	30fps / 25fps(60Hz / 50Hz)
Min. Illumination	Color : 0.11Lux(F1.6)(30IRE) BW : 0Lux(IR LED on)
Video Out	BNC(AHD / TVI / CVI / CVBS Selectable)
Video Transmission Distance	500m(5C2V Coaxial Cable)

Lens

Focal Length (Zoom Ratio)	3.2~10mm(3.1x) manual varifocal
Max. Aperture Ratio	F1.6
Angular Field of View	H: 110.2°(Wide) ~ 32°(Tele) / V: 55.4°(Wide) ~ 18°(Tele) / D: 128.4°(Wide) ~ 36.6°(Tele)
Min. Object Distance	0.5m(1.64ft)
Focus Control	Manual
Lens Type	DC auto iris

Operational

Camera Title	Displayed up to 15 characters
Day & Night	Auto(ICR)
Backlight Compensation	BLC, HLC, WDR
Wide Dynamic Range	120dB
Digital Noise Reduction	SSNRIV
Defog	Support
Motion Detection	4ea
Privacy Masking	8ea, rectangular zones
Gain Control	Low / Middle / High / Very High
White Balance	ATW / AWC / Manual / Indoor / Outdoor
Electronic Shutter Speed	1 ~ 1/12,000sec
Video Rotation	H-Rev / V-Rev
Analytics	Motion detection
Alarm I/O	MD output 1ea
Alarm Triggers	Analytics
Alarm Events	Alarm output
IR Viewable Length	30m(98.43ft)
Coaxial Protocol	ACP(AHD Coax Protocol), TCP(TVI Coax Protocol), CCP(CVI Coax Protocol) CVBS : Pelco-C(Coaxitron)

Environmental & Electrical

Operating Temperature / Humidity	-30°C ~ +55°C(+22°F ~ +131°F) / Less than 90% RH
Certification	IP66, IK10
Input Voltage	24VAC, 12VDC
Power Consumption	Max 6W

Mechanical

Color / Material	Dark grey / Aluminum
Product Dimensions / Weight	Ø78.0x259.8mm(3.07x10.23"), 914g(2.02 lb)

HCO-6070R

1080p аналоговая HD
цилиндрическая камера с ИК-
подсветкой



CAD

Unit: mm [inch]

