



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	DRAWN
	A	圖面繪製申請 SL19001	01/09'19	JOY

COMPONENTS		
ITEM	PART NAME	Q'TY
1	PCB Module	1
2	LATCH	1
3	JAW1	1
4	JAW2	1
5	CAP Module	1
6	Nut	1
7	Wiring Lable-DOWN	1
8	Wiring Lable-UP	1

TRANSMISSION PERFORMANCE
 Meet all requirements specified in Patch Cord requirement of:
 ANSI/TIA-568-C.2, Category 5e

ELECTRICAL
 Electrical Insulation Resistance : 500MΩ min. @100V d.c
 Dielectric Withstanding Voltage : 1000V D.C or A.C Peak,

MECHANICAL
 IDC Wire Gauge : 23 ~ 26 AWG

PHYSICAL
 Housing : High-Impact, Flame-Retardant Plastic, UL 94V-0
 Contact pin : Phosphor Bronze Alloy Plated With 50 micro-inch of Gold
 IDC : Phosphor Bronze Alloy With 100 micro-inch 100% Sn Alloy

UNLESS OTHERWISE SPECIFIED TOLERANCES		PROJECT #		EUROLAN	
FINISH	APPROVED	13A-U5-03GY	DATE		
SURFACE	CHECK	FILE	TITLE	CAT 5e UTP Field Terminable Plug	
DATE	APPROVED	DRAWN	DATE	SIZE	DRAWING NUMBER
1/9/19	JOY	01/09'19		A4	
		SCALE		UNIT	SHEET
		1 : 1		mm	1 of 1